

TECHNICAL DATA SHEET

EnviroDri® Brick Ledge

Cold-Applied, Self-Adhering Membrane

PRODUCT DESCRIPTION

EnviroDri® Brick Ledge is a cold-applied, self-adhering membrane composed of a triple woven polypropylene on one side and a layer of butyl-modified asphalt on the other. This product fully integrates with the EnviroDri Weather-Resistant Barrier System to provide you with the next level of protection against air and moisture intrusion. This product can also be used with our standard below-grade waterproofing products and systems to protect the brick ledge from moisture intrusion.

BASIC USES

Seals brick ledge from moisture intrusion. Can be used with EnviroDri Weather Resistant Barrier Systems and Tremco's waterproofing products.

FEATURES & BENEFITS

- · Fully adhered system
- · Seals around brick ledge
- Forms a positive air/vapor barrier
- 6-month UV exposure rating
- Excellent overlap adhesion

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit https://www.tremcosealants.com/warranties/ for details.

TYPICAL PHYSICAL PROPERTIES		
PROPERTY	DESCRIPTION	
Color	Black	
Thickness	40 mils	
Packaging	Roll Width: 12" (3 rolls/carton) 18" (2 rolls/carton)	Roll Length: 66'
Application	Apply at temperatures 20 °F or higher	
Storage	Store in an unopened container at between 50-90 °F	
PROPERTY	TEST METHOD	TYPICAL RESULTS
Tensile Strength	ASTM D412	>1600 psi
Elongation (Adhesive Only)	ASTM D412	500%
Permeance	ASTM E96	<0.5
Low Temperature Flex	ASTM D1970	No Cracks or Delamination
Nail Salability	ASTM D1970	Pass

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements. EDBLDS/0623 TREMCO