



# TECHNICAL DATA SHEET

## EnviroDri Pan & Arch

Cold-Applied Self-Adhering Membrane

### PRODUCT DESCRIPTION

EnviroDri® Pan & Arch is a multi-directionally flexible, cold-applied, self-adhering membrane composed of butyl rubber with a creped, cross-laminated polyolefin liner. This product conforms easily and effectively to curved substrates. Because of its unique design, EnviroDri Pan & Arch provides an air- and moisture-tight seal and eliminates the need for corner flashing patches. EnviroDri Pan & Arch fully integrates with the EnviroDri Weather-Resistant Barrier System to provide you with the next level of protection against air and moisture intrusion.

### FEATURES & BENEFITS

- 75' long roll, with 6" and 8" widths available
- Butyl-based material offering exceptional adhesion to most building materials
- Specifically engineered and designed to provide an air and moisture seal around arched and curved door and window openings
- Flexible design eliminates the need for separate corner flashing patches on sides of window openings
- Integrates seamlessly with the EnviroDri Field Membrane
- Resists UV degradation for up to 1 year or direct sun exposure
- Provides strong and immediate adhesion over a wide range of installation temperatures, and remains pliable at low temperatures

### WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

### TYPICAL PHYSICAL PROPERTIES

PROPERTY	DESCRIPTION	
Color	White	
Application Temperature Range	20 - 180 °F	
Packaging	Roll Width: 6" (1 roll / carton) 8" (1 roll / carton)	Roll Length: 75'
Storage	8.2 + 0.15 lbs./gal	Store in an unopened container between 60-80 F°
PROPERTY	TEST METHOD	TYPICAL RESULTS
Thickness	ASTM D1000	50 mils
Tensile Strength (Cross)	ASTM D412-9	>400 psi
Tensile Strength (Machine)	ASTM D412-9	>295 psi

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

**NOTE:** All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

EDPADS/0623

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



[tremcosealants.com](http://tremcosealants.com) | 800.321.7906



*Construction Products Group*

3735 Green Rd. | Beachwood, OH 44122  
800.321.7906 | [tremcocpg.com](http://tremcocpg.com)